Engine

| Engine Type | Aluminum-alloy in line 4-cylinder |
|-----------------------|---|
| Displacement (liters) | 2.0 |
| Horsepower (SAE net) | RSX: 155 bhp @ 6500 rpm Type-S: 201 bhp @ 7800 rpm |
| Torque | RSX: 139 lbs-ft @ 4000 rpm Type-S: 140 lbs-ft @ 7000 rpm |
| Redline | RSX: 6800 rpm Type-S: 8100 rpm |
| Compression Ratio | RSX: 9.8:1 Type-S: 11.0:1 |
| Fuel Injection | PGM-FI Multi-Point Injection |
| Emmissions | LEV-2 CARB |

^{*} For 2006, Acura is complying with the new SAE standards for measuring horsepower and torque. This new method slightly reduces a vehicle's horsepower rating and torque due to more stringent testing procedures.

| Transmission |
|---|
| RSX Manual |
| 5-speed manual |
| Gear ratios (:1) |
| 1st |
| 2nd |
| 3rd |
| 4th |
| 5th |
| Reverse |
| Final Drive |
| |
| RSX Automatic |
| 5-Speed automatic with Sequential SportShift and GradeLogic Control |
| Gear ratios (:1)RSX Automatic |
| 1st |
| 2nd |
| 3rd |
| 4th |
| 5th |
| Reverse |
| Final Drive |
| |
| Type-S |
| Close-ratio 6-speed manual |
| Gear ratios (:1) |
| 1st |
| 2nd2.13 |
| 3rd |
| 4th |
| 5th |
| 6th |
| Reverse |
| Final Drive |

Chassis

| Е | Body Type | Uni-body |
|---|--|--|
| S | Suspension | Front Control-Link MacPherson Strut/Rear Double Wishbone |
| S | Stabilizer Bar (front/rear) | RSX: 25.4 mm tubular front/19.0 mm solid rear |
| | | Type-S: 26.5 mm tubular front/21.0 mm solid rear |
| S | Steering Type | Variable power-assist rack-and-pinion |
| Т | Furning Diameter, curb to curb | 38.1 ft |
| V | Wheels | RSX: 16 x 6.5 aluminum-alloy |
| | | Type-S: 17 x 7.0 aluminum-alloy |
| Е | Brakes: 4-Wheel Disc with ABS (front/rear) | RSX: 10.3" ventilated/10.2" solid |
| | | Type-S: 11.8" ventilated/10.2" solid |
| Т | Tires | RSX: P205/55 R16 89V All-Season |
| | | Type-S: P215/45 R17 87V All-Season |

General Specifications

| EPA Estimated Fuel Mileage (city/hwy) | RSX: 5-Speed Manual: 27/34 mpg RSX: 5-Speed Automatic: 25/34 mpg Type-S: 6-Speed Manual: 23/31 mpg |
|--|---|
| Fuel Tank Capacity | 13.2 U.S. gallons (50 liters) |
| Recommended Fuel | RSX: Regular unleaded 86 octane Type-S: Premium unleaded 91 octane |
| Crankcase Refill Capacity, incl filter | RSX: 4.4 U.S. quarts (4.2 liters) Type-S: 5.0 U.S. quarts (4.7 liters) |
| Cooling System Capacity | RSX: 6.8 U.S. quarts (6.4 liters) Type-S: 7.1 U.S. quarts (6.7 liters) |
| Minimum Ground Clearance | RSX: 6.0 in (152 mm) Type-S: 5.9 in (149 mm) |
| Curb Weight | RSX: Manual: 2734 lbs (1240 kg) RSX: Automatic: 2809 lbs (1274 kg) Type-S: Type-S: 2840 lbs (1288 kg) |
| Weight Distribution (% front/rear) | RSX: Type-S: Manual 61/39 RSX: Automatic 62/38 |
| Head Room | Front: 37.8 in (960 mm) |
| Leg Room | Front: 43.1 in (1094 mm) |
| Hip Room | Front: 51.1 in (1297 mm) |
| Shoulder Room | Front: 52.6 in (1337 mm) |
| EPA Passenger Volume | 81.9 cu. ft. |
| EPA Cargo Volume | 16.0 cu. ft. |

Remote entry system

| Inter | ior Features |
|-------|--|
| Spor | t seat with cloth-trimmed interior |
| Spor | t seats with perforated leather-trimmed interior (standard on Type-S, option on base RSX) |
| Drive | er's seat adjustable lumbar support |
| Drive | er's seat-height adjustable |
| Leath | ner-wrapped steering wheel |
| Titan | ium finished gearshift knob |
| White | e-faced gauges with red illumination |
| Front | t center console with tray and dual beverage holder |
| Light | ed front beverage holder area |
| 50/50 | O split fold-down rear seatback |
| Rear | -seat center storage and tray |
| Three | e rear beverage holders |
| Cent | er console front and rear power outlets |
| Drive | er's and front passenger's seatback pockets |
| Front | t passenger-side walk-in feature |
| Carp | eted floor mats |
| 12-v | olt power outlets (front and rear) |
| Rem | ovable cargo cover |
| Dual | trip meters |
| Main | tenance interval reminder |
| Illum | inated power window switches and ignition switch |
| Integ | rated glass antenna |
| Titan | ium trim in front seat headrest opening |
| Textu | ured titanium instrument panel |
| Chro | me trim ring around manual transmission shift boot |
| Powe | er moonroof with tilt and key-off operation |
| Acura | a Surround Sound with AM/FM tuner, in-dash CD Player, 6 speakers and anti-thief feature |
| | a/Bose® Surround Sound with AM/FM tuner, cassette, 6-disc in-dash CD changer, 7 speakers, including bass® woofer, and anti-thief feature |
| Anti- | deterrent system with electronic immobilizer |
| Auto | matic climate control system |
| Powe | er windows, door locks and hatch lock |
| Drive | er's auto up/down window with auto-reverse |
| Stee | ring wheel-mounted cruise control |
| Front | t door storage pockets |
| Dual | overhead map lights |

Chip-resistant rocker panels

Exterior Features

| Exterior Features |
|--|
| Heated, power-operated, body-colored outside mirrors |
| Remote entry system |
| 16-inch aluminum alloy wheels |
| 17-inch aluminum alloy wheels |
| All-Season steel-belted radial tires |
| Heat-rejecting green-tinted glass |
| Galvanized-steel body panels |
| Body-colored front and rear bumpers |
| Body-colored hatch spoiler |
| Body-colored chin spoiler and exclusive lower side sills |
| Body-colored rockers |
| Speed-sensing, variable intermittent windshield wipers |
| Rear window wiper and washer |
| Integrated rear glass antenna |
| Chrome exhaust outlet |
| Billet-style exhaust outlet |
| Sport-tuned suspension |
| Body-colored chin spoiler and lower side sills |

All-around visibility (289.0 degrees)

Safety Features

| outer, routered |
|--|
| Dual-stage, dual-threshold front airbags (SRS) |
| Front side airbags with passenger-side Occupant Position Detection System (OPDS) |
| 3-point seatbelts with load limiters and pretensioners (front) |
| 3-point seat belts (rear) |
| 4-wheel disc brakes with anti-locking braking system |
| 5-mph bumpers (front/rear) |
| LATCH (Lower Anchors and Tethers for Children) child-seat mounting system |
| Impact-absorbing crumple zones (front and rear) |
| Multi-reflector halogen headlights |
| Rear-window defroster with timer |
| Front-side window defogger |
| Side-impact door beams |
| Side-impact floor beams |
| Front side-window defogger |
| Collapsible steering column |
| Impact-absorbing interior surfaces |
| Safety glass |
| Nonprotruding switches and controls |
| Automatic transmission interlock features |
| Center high-mount brake light |
| |

2006 RSX Specifications

AHEAD OF THE CURVE

Warranties

| Vehicle | 4-year/50,000-mile limited warranty * |
|---|--|
| Powertrain | 6-year/70,000-mile limited warranty * |
| Outer Body Rust-through | 5 year/unlimited-mile limited warranty * |
| Accessories | 4 year/50,000-mile limited warranty ** |
| No askeduled true true required for 100,000 miles or more *** | |

No scheduled tune-ups required for 100,000 miles or more ***

^{*}Ordinary maintenance items or adjustments, parts subject to normal wear and replacement, and certain other items are excluded.

^{**}When installed at the time of new-vehicle delivery.

^{***}Does not apply to fluid and filter changes or periodic inspections. Please refer to the maintenance section of your owner's manual to determine all appropriate maintenance intervals.

2006 RSX Specifications

AHEAD OF THE CURVE

| Intorio | r Acces | CATIOC |
|----------|---------|--------|
| IIIICIIO | I ALLES | aviica |

CD Changer

CD Changer Magazine

CD Changer Attachment

All Season Floor Mats, Black and All Season Floor Mats, Grey

Aluminum Shift Knob 5MT

Aluminum Shift Knob (Type-S only)

Cassette Player

Trunk Tray

Cargo Net

Interior Trim

Exterior Accessories

Car Cover

Full Nose Mask

Front Under Body Spoiler

Side Under Body Spoiler

Rear Under Body Spoiler

High Wing Spoiler

High Wing Spoiler with Lid

Rear Wing Spoiler

Moonroof Visor

Wheel Locks

Engine Block Heater

Fenderwell Trim

Gold Emblem Kit

Fog Lights

Splash Guards

16" Machined Finish 7-Spoke Aluminum-Alloy Wheels

17" Machined Finish 10-Spoke Aluminum-Alloy Wheels

Gold "Type-S" Emblem