



Sometimes you want
complicated.



Sometimes you don't.

Lexmark **X3330**

High Definition All-in-One

- High quality black, colour & borderless prints up to 4800 dpi (from 10x15cm up to A4)
- High definition scanner (48 Bit/600x2400 dpi)
- Produces black & colour copies without a PC
- Direct camera printing with PictBridge
- Produces stunning photos that last for generations* with the optional evercolor™ inks Photo Cartridge No. 31 & Lexmark Premium Glossy Paper
- Borderless 6-colour photo capable

* Based on fade resistance testing of prints displayed or stored under appropriate conditions. Contact Lexmark for details.

High Quality
Prints

Easy Copying
System

We make printing easy

LEXMARK

Lexmark X3330

FEATURES

Print

• Resolution:		
Mode (dpi)	Glossy paper	Plain paper
Best	4800 x 1200	2400 x 1200

- Ink drop size: 24 pL black drop size
3/10 pL colour drop size
- Acoustics: 49 dBA or less
- Duty cycle: 1 000/month
- Print Technology: Thermal Inkjet 4 Colour
Cyan, Magenta, Yellow, Black

• Speed:	
Mode	Quick (ppm)
Black	Up to 22
Colour	Up to 15

Scan

- Resolution: 600 x 2400 dpi (optical)
- Colour depth: 48 bits internal True Colour
24 bits external True Colour
- Scan area : 216 mm x 297 mm
- Removable Cover: Yes
- Acoustics: 37 dBA or less
- Scan Technology : CIS

Copy

- PC free copy
- Up to 99 copies at one time (selectable via computer)
- Reduce/Enlarge: 25% to 400% selectable via computer
- Acoustics: 40 dBA or less
- Speed:
- Mode Quick (ppm)
- Black Up to 15
- Colour Up to 9



TECHNOLOGY

Supply

BLACK CARTRIDGE

- No. 32: up to 200 pages* at 5% coverage
Also compatible with Black cartridge No. 34

COLOUR CARTRIDGE

- No. 33: up to 190 pages** at 15% coverage
Also compatible with Colour cartridge No. 35
For enhanced photo quality change the No. 32 Black for the Photo Cartridge No. 31



Miscellaneous

- Max. paper weight: 500 gsm
- Input/Output tray: up to 100 sheets/ 25 sheets
- Paper Handling Technology: Accu-Feed™
- Memory: 16 SDRAM
- Interface: USB 2.0 Full Speed
- Lexmark guarantee: 1 year on-site exchange
- Windows 98, ME, 2000, XP, Mac OS X, 10.2.3 thru 10.2.8, 10.3.0 thru 10.3.x
- Power requirements: 220v-240v input voltage

Minimum system requirements:

Operating system	Processor Speed (Mhz)	RAM (MB)	Hard disc space (MB)	Virtual Memory (MB)
Windows 98	Pentium II 233	128	500	NA
Windows ME	Pentium II 233	128	500	NA
Windows 2000	Pentium II 233	128	500	286
Windows XP	Pentium II 300	128	500	300
Mac OS X, 10.2.3 thru 10.2.8, 10.3.0 thru 10.3.x	G3400	128	300	NA

LOGISTICAL INFORMATION

In the box

- Lexmark X3330
- Power Supply + Line Cord
- 1 High Resolution Black Cartridge No. 32
- 1 High Resolution Colour Cartridge No. 33
- Set up Guide
- Installation CD
- Driver Software for Mac and Windows
- Lexmark Imaging Studio Software
- Service and Guarantee Information

Weight and dimensions

- Machine retracted: Width 441.00 mm, Depth 319.00 mm, Height 172.00 mm
- Machine extended: Width 441.00 mm, Depth 530.00 mm, Height 287.00 mm
- Machine weight: 4.54 kg (excluding power supply & printhead)
- Packaged weight: 5.65 kg
- Packaging dimension: Width 499.87 mm, Depth 232.91 mm, Height 405.89 mm

* Estimated yield based on page coverage of 5% text. Based on average results obtained during plain paper, normal mode printing. Actual page yield may vary. Contact Lexmark for more details.

** Estimated yield based on page coverage of 5% cyan, 5% magenta, 5% yellow. Based on average results obtained during plain paper, normal mode printing. Actual page yield may vary. Contact Lexmark for more details.