

linear-slide switches



- slide up to on, down to off
- use with any 20A load
- no derating if ganged

general purpose switches (small control)

single pole	120V/277V	20A	NT-1PS-
3-way	120V/277V	20A	NT-3PS-
4-way	120V/277V	20A	NT-4PS-

switching for AC motorized shades and projection screens



- double-pole, double-throw switches for lower/center-off applications
- no derating if ganged
- provides momentary or maintained switching function

general purpose switches (small control)

momentary			NT-DPDT-CO-MO-
120V/277VAC	30A		
2HP@120/240VAC			
maintain			NT-DPDT-CO-MA-
120V/277VAC	15A		
1/2HP@120VAC;			
2HP@240VAC			

slide-to-off fan controls



- slide up to on/increase speed, down to decrease/off
- no derating if ganged
- for use with only one ceiling paddle fan

quiet 3-speed control (small control)

single pole fan control	1.5A	NTFSQ-
-------------------------	------	---------------

slide-to-off fan controls



- slide up to on/increase speed, down to decrease/off
- small control shown
- large control measures 4.56" x 4.56" (fits into a 1-gang backbox)
- for use with multiple ceiling paddle fans or exhaust fans
- must be derated if ganged

fully variable control (small control)

single pole fan control	6A	NTFS-6E-
-------------------------	----	-----------------

fully variable control (large control)

single pole fan control	12A	NTFS-12E-
-------------------------	-----	------------------

See page 23 for available colors.

To order, add color suffix to model number.

Example: **NT-1PS- WH**



Shown actual size: Nova T[☆] dimmer in satin nickel (SN) (includes wallplate)

NOVA T[☆] dimmers

product family features

- exclusive dimmer/switch size opening
- slide adjusts light to suit any activity
- classic slider, thin-profile design
- full family of controls plus matching fan controls, switches and wiring devices
- dimmer includes 1-gang wallplate
- use “no fins broken” wallplates for full wattage capacity in multi-gang applications
- voltage compensation maintains stable light levels despite line voltage variations

Questions on installation or selection?
Call Lutron® 24 hours/7 days a week at
1.800.523.9466 or visit www.lutron.com

available models

source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- neon/cold cathode
- fluorescent lighting
- LED lighting
- quiet 3-speed fan controls
- fully variable fan controls
- motorized window treatments

control locations

- single pole (one location)
- 3-way (two locations)
- 4-way switches (three locations) available

available colors

(see page 14 for color swatches)

colors (architectural matte finish)

- | | |
|------------------------|------------------|
| WH white | GR gray |
| BE beige | TP taupe |
| IV ivory | BR brown |
| AL almond | BL black |
| LA light almond | SI sienna |

metals (special finishes)

- | | |
|--------------------------|-------------------------|
| SB satin brass | SC satin chrome |
| BB bright brass | SN satin nickel |
| BC bright chrome | BN bright nickel |
| QB antique brass | AU gold plated |
| QZ antique bronze | |

anodized aluminum

- | | |
|------------------|------------------|
| CLA clear | BRA brass |
| BLA black | |

Custom colors and finishes are available by providing Lutron® with a paint color number, swatch, or sample. Lutron® can color match your controls. Contact Customer Service at 1.888.LUTRON1.

Multi-gang, screwless, seamless wallplates available – wallplate selector tool at www.lutron.com/lutron/wallplate

CAD file downloads available at www.lutron.com/cad