

# NEW! Maytag® Room Air Conditioners

## Cool Comfort and Dependable Quality.

Looking for relief from the heat? Introducing the new line of Maytag Room Air Conditioners. You'll stay cool and comfortable all season. And standard features like a slide-out, washable filter and protective rear grille ensure years of dependable cooling.

- AccuTemp™ Temperature Control is Accurate to  $\pm 2^{\circ}\text{F}$
- 4-Way Air Direction Lets You Control the Airflow\*
- Exhaust Vent Helps Circulate Fresh Outdoor Air\*
- Start Assist Gives Unit a Boost During "Brown-Outs"
- Slide-Out Chassis Allows for Easy Installation On Large Sizes

*\* features vary on 5,000 BTU models*

Electronic touch control models pack even more convenient features:



**Digital Display** – Shows set temperature

**One Degree Temperature Adjust** – Lets you set the exact room temperature

**Filter Check Reminder** – Lights when filter needs cleaning\*

**24-Hour Timer** – Allows unit to be turned on/off at a predetermined time

**AutoCool Setting** – Automatically adjusts fan speed according to room temperature

**Energy Save Mode** – Maintains room temperature while saving energy\*

**Remote Control** – Operates the unit from a distance



TOLL-FREE ASSISTANCE **1-866-MAYTAG-1**



**5** YEARS

**Dependable Performance™ Warranty†**

†refer to owner's manual for warranty information

# Introducing Maytag Room Air Conditioners.

## M3X05F2A



- 5,000 BTUs
- Cools rooms up to 150 sq. ft.
- 2 cool & 2 fan speeds
- 5-Year Dependable Performance™ Warranty

## M6X05F2A



- 5,000 BTUs
- Cools rooms up to 150 sq. ft.
- 2 cool & 2 fan speeds
- **Electronic touch control**
- 5-Year Dependable Performance™ Warranty

## M3Q06F2A • M3Q08F2A • M3Q10F2A



- 6,000 to 10,000 BTUs
- Cools rooms 200 to 450 sq. ft.
- 3 cool & 2 fan speeds
- 5-Year Dependable Performance™ Warranty

## M6Q06F2A • M6Q08F2A • M6Q10F2A



- 6,000 to 10,000 BTUs
- Cools rooms 200 to 450 sq. ft.
- 3 cool & 3 fan speeds
- **Electronic touch control**
- 5-Year Dependable Performance™ Warranty

## M3T12F2A



- 12,000 BTUs
- Cools rooms 550 sq. ft.
- 3 cool & 2 fan speeds
- 5-Year Dependable Performance™ Warranty

## M6T12F2A



- 12,000 BTUs
- Cools rooms 550 sq. ft.
- 3 cool & 3 fan speeds
- **Electronic touch control**
- 5-Year Dependable Performance™ Warranty

## M3D16E2A • M3D18E7A • M3D24E7A



- 16,000 to 24,000 BTUs
- Cools rooms 850 to 1400 sq. ft.
- 3 cool & 2 fan speeds
- 5-Year Dependable Performance™ Warranty

## M6D16E2A • M6D18E7A • M6D24E7A



- 16,000 to 24,000 BTUs
- Cools rooms 850 to 1400 sq. ft.
- 3 cool & 3 fan speeds
- **Electronic touch control**
- 5-Year Dependable Performance™ Warranty

| SPECS/FEATURES           | M3X05F2A | M6X05F2A | M3Q06F2A | M6Q06F2A | M3Q08F2A | M6Q08F2A | M3Q10F2A | M6Q10F2A | M3T12F2A | M6T12F2A | M3D16E2A | M6D16E2A | M3D18E7A | M6D18E7A | M3D24E7A | M6D24E7A |
|--------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| BTU Size                 | 5,000    | 5,000    | 6,000    | 6,000    | 8,000    | 8,000    | 10,000   | 10,000   | 12,000   | 12,000   | 16,000   | 16,000   | 18,000   | 18,000   | 24,000   | 24,000   |
| Room Area (Square Feet)  | 150      | 150      | 200      | 200      | 340      | 340      | 450      | 450      | 550      | 550      | 850      | 850      | 1,000    | 1,000    | 1,400    | 1,400    |
| EER                      | 9.7      | 9.7      | 9.7      | 9.7      | 9.8      | 9.8      | 9.8      | 9.8      | 9.8      | 9.8      | 10.5     | 10.5     | 9.8      | 9.8      | 8.5      | 8.5      |
| Plug Type                | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 125V/15A | 250V/15A | 250V/15A | 250V/20A | 250V/20A |
| Window Width (Min/Max)   | 19"-36"  | 19"-36"  | 20¼"-39" | 20¼"-39" | 20¼"-39" | 20¼"-39" | 20¼"-39" | 20¼"-39" | 24"-39"  | 24"-39"  | 26¾"-40" | 26¾"-40" | 26¾"-40" | 26¾"-40" | 26¾"-40" | 26¾"-40" |
| Window Height (Min)      | 12¾"     | 12¾"     | 13"      | 13"      | 13"      | 13"      | 13"      | 13"      | 16¼"     | 16¼"     | 18½"     | 18½"     | 18½"     | 18½"     | 18½"     | 18½"     |
| Air Direction            | 2        | 2        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        | 4        |
| Cool Speeds              | 2        | 2        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        | 3        |
| Fan Speeds               | 2        | 2        | 2        | 3        | 2        | 3        | 2        | 3        | 2        | 3        | 2        | 3        | 2        | 3        | 2        | 3        |
| Slide-Out Filter         | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        |
| Air Exchanger            |          |          | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        |
| AccuTemp™ Thermostat     | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        |
| Protective Rear Grille   | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        | ■        |
| Electronic Touch Control |          | ■        |          | ■        |          | ■        |          | ■        |          | ■        |          | ■        |          | ■        |          | ■        |
| Slide-Out Chassis        |          |          |          |          |          |          |          |          |          |          | ■        | ■        | ■        | ■        | ■        | ■        |
| Start Assist             | ■        | ■        | ■        |          |          |          |          |          |          |          |          |          |          |          |          |          |

Because of continuous product improvement, we reserve the right to change specifications without notice. All room air conditioners are UL-approved.



MAYTAG ROOM AIR CONDITIONERS • 415 WABASH AVE • EFFINGHAM, IL 62401

Maytag is a registered trademark of the Maytag Corporation and is used under license by Fedders North America, Inc.