

Present with Confidence

"Nobo Digital DLP® projectors provide high resolution, high contrast imaging and exceptional brightness ratings. The sharp image quality and ease of use operation make these lightweight, portable projectors suitable for all presentation requirements."



NOBO DLP® Projectors

X22C XGA Resolution

S22E SVGA Resolution

- Exceptionally bright 2200 lumens
- Superb 2000:1 contrast ratio
- Eco mode facility extends lamplife and reduces the noise decibels for quieter presentations
- 3000/2000 hours lamp life (ECO/Brightmode)
- Impressively quiet at 30/32 dB (ECO/Brightmode)
- Robust and lightweight at only 2Kgs
- 1W internal speaker
- Save time with express power on & shutdown feature
- Added security with password protection and Kensington lock facility
- Simple Plug and Play



- The X22C not only offers fantastic looks and style but also great performance. Super-bright 2200 lumens, 2200:1 contrast ratio and great XGA picture quality with striking realistic colour enhances business presentations. Suitable for medium to larger-sized meeting rooms.
- Under its sleek design the S22E is accomplished SVGA multitasker suitable for small to medium-sized meeting rooms and education endeavours when displaying basic data and simple graphics.
- Both DLP machines have an Auto power-off feature that shuts down the projector when not in use, saving power and increasing lamp life.
- A 15 second start-up and cool down time helps to reduce time and energy use as well.
- With Kensington lock facility and password protection for added security and peace of mind.
- These new DLP machines are both robust and lightweight at only 2Kgs and as versatile on the move as when installed.

X22C DLP®

S22E DLP®

Specifications

Product code	1902414	1902413
Display Technology:	Single 0.55" XGA Type-X DMD chip DLP® Technology from Texas Instruments	Single 0.55" SVGA Type-X DMD chip DLP® Technology from Texas Instruments
Resolution:	Native XGA (1024 x 768)	Native SVGA (800 x 600)
Brightness:	2200 ANSI Lumens	2200 ANSI Lumens
Contrast:	2200:1	2000:1
Noise Level:	30/32 dB	30/32 dB
Aspect Ratio:	4:3 Native, 16:9 Compatible	4:3 Native, 16:9 Compatible
Colour Wheel	RGBWY	RGBWY
Weight:	~ 2kg	~ 2kg
Video Compatibility:	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i)	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i)
Keystone Correction:	Vertical	Vertical
Lamp Type:	180W (User Replaceable)	180W (User Replaceable)
Lamp Life:	3000/2000 Hours (STD/Bright Mode)	3000/2000 Hours (STD/Bright Mode)
Dimensions: (W x D x H)	259 x 188 x 71.5 mm	259 x 188 x 71.5 mm
INPUTS		
DVI-I	DVI-I HDCP (HDMI via optional adapter)	-
PC RGB	1 x 15 Pin D-Sub VGA	1 x 15 Pin D-Sub VGA
Analogue Component	15 Pin D-Sub VGA (Via optional adaptor)	15 Pin D-Sub VGA (Via optional adaptor)
S-Video	4 pin Mini DIN	4 pin Mini DIN
Composite	Via optional Y-TYPE Composite to S-video Adapter	Composite
Stereo Audio	Mini Jack	Mini Jack
Serial Control	RS232 - 3 Pin	-
OUTPUTS		
PC	15 Pin D-Sub (monitor loop-through)	-
USB	For Remote Mouse Function	For Remote Mouse Function
Audio	1 x 1W Speaker	1 x 1W Speaker
Security:	1 Kensington Lock Port, Password Protection	1 Kensington Lock Port, Password Protection
Remote control:	Remote Mouse Function & Direct Source Selecting	Remote Mouse Function & Direct Source Selecting
Standard Accessories:	AC Power Cord, VGA Cable, Infra-Red Remote Control, Batteries x 2, CD + Quick Start Card for User Manual, Warranty Card, WEEE card, Soft Carry Bag	AC Power Cord, VGA Cable, Composite Video Cable, Infra-Red Remote Control, Batteries x 2, CD + Quick Start Card for User Manual, Warranty Card, WEEE card, Soft Carry Bag

For more detailed specification and information on other NOBO digital DLP® projectors visit www.noboprojection.com



All NOBO MultiMedia products are covered by NoboGuard, our premium projector protection scheme, which includes a three year product warranty and one year lamp warranty for complete piece of mind.

